

Visual Computations, Geometry, and Visual Cortex


R. Coifman, V. Rokhlan, and Steven W. Zucker

Yale University


Distribution A, Approved for Public Release, Distribution Unlimited

The Motivation for Edge Detection


Edges are considered to be stable features of objects in images, *e.g.*, with respect to variable illumination.



An image of a Klein bottle.




The same object illuminated differently.



The patch X under different illuminations.

The Motivation for Edge Detection

In image space, the edge patches lie near a low-dimensional manifold.



ψ_1



ψ_2



ψ_3





Distribution A, Approved for Public Release, Distribution Unlimited


The Edge Manifold

A simple edge model:

$$f(x, y; \theta) = \begin{cases} 1 & \text{if } -\sin(\theta)x + \cos(\theta)y > 0 \\ 0 & \text{otherwise} \end{cases}.$$



Distribution A, Approved for Public Release, Distribution Unlimited








Given an image:

2. Split this image into local patches: to each pixel of the image, associate its 8x8 pixel neighborhood.
3. Treat these windows as a dataset of points in 64 dimensions. Compute the prolates on this set.
4. Find local coordinate systems on the set.


Distribution A, Approved for Public Release, Distribution Unlimited

A simple example: black disk on white background:




Above are represented the first 4 prolates in the image space (image domain vs. prolates value).

2. Prolates 1 and 2 capture the ratio of black pixels over white pixels.
3. Prolates 3 and 4 capture the angle θ
4. Locally, 2 prolates are sufficient to describe the data




To each point in the dataset (or to each pixel in the image) we associate its coordinates in the (ϕ_2, ϕ_3, ϕ_4) system.




Plot of a selected subset of windows in (ϕ_2, ϕ_4)

- ϕ_2 measures the proportion of black pixels
- ϕ_4 measures the orientation of the edge





Distribution A, Approved for Public Release, Distribution Unlimited

"Ice cube" model of cortical columns



Distribution A, Approved for Public Release, Distribution Unlimited


Curve coherence: computational and biological perspectives



Gilbert, Neuron 1989



Gilbert & Wiesel, J. of Neuroscience, 1983

Distribution A, Approved for Public Release, Distribution Unlimited








Distribution A, Approved for Public Release, Distribution Unlimited

Cocircularity coherence in the orientation hypercolumn ($XY\theta$) architecture




Distribution A, Approved for Public Release, Distribution Unlimited

Cocircularity-based curve inference




Distribution A, Approved for Public Release, Distribution Unlimited

Cocircularity-based curve inference






Distribution A, Approved for Public Release, Distribution Unlimited

Visual flow coherence in the orientation hypercolumn ($XY\theta$) architecture




Distribution A, Approved for Public Release, Distribution Unlimited


Shading flow field relaxation



Distribution A, Approved for Public Release, Distribution Unlimited





Distribution A, Approved for Public Release, Distribution Unlimited



Distribution A, Approved for Public Release, Distribution Unlimited

Computational abstraction



Distribution A, Approved for Public Release, Distribution Unlimited

“Games Neurons Play”

Consider neurons as “players” in a polymatrix game. Their strategies are whether to fire or not to fire.

Relaxation Labeling	Game Theory	Notation
nodes	players	i, j, \dots, k
labels	strategies	λ
probabilistic labeling	mixed strategy	$p_i(\lambda)$
compatibilities	payoff matrix	$r_{i,j}(\lambda, \lambda')$
consistent labeling	Nash equilibrium	$\text{Grad } A(P) = 0$

Goal: select labels (strategies) λ at each node (neuron) to extremize:



$$A(P) = \sum_{i,\lambda,j,\lambda'} p_i(\lambda) r_{i,j}(\lambda, \lambda') p_j(\lambda')$$

such that

$$\sum_{\lambda} p_i(\lambda) = 1; 0 \leq p_i(\lambda) \leq 1$$


Computational Strategies for LCP's

Computing with cliques of neurons





Distribution A, Approved for Public Release, Distribution Unlimited

Acuity and hyperacuity



Distribution A, Approved for Public Release, Distribution Unlimited

Hyperaccurate receptive fields and reliability



Distribution A, Approved for Public Release, Distribution Unlimited